

DesignWood

JONES 
WHOLESALE LUMBER

Pre-Colored ACQ Treated Lumber

Sedona Red

SAVE CUSTOMERS TIME & MONEY

LESS STAINING ... MORE ENJOYING

DesignWood color is part of the
pressure-treating process



Proud Sponsor

AWPA
Standardized
For Proven Performance
www.awpa.com

Look for AWPA U1
and the Checkmark of Quality



A Finished Project From The Start

- The DesignWood colorant* is pressure impregnated with the preservatives, giving color and protection in one step.
- Eliminates the need for initial staining, saving time and money.
- Ideal for decks, docks, bridges, pole-type buildings, structural-framing lumber, fence posts, and landscaping.

Proven Soluble Copper Preservative

- Preserve® ACQ® treated wood meets the stringent industry standards of the American Wood Protection Association (AWPA), the leading authority on wood preservation science.
- The International Code Council's committees recognize AWPA Standards directly in the model building codes (IBC and IRC) for residential and commercial applications.
- Preserve® ACQ® improves the durability of exterior wood for sustainable building; field-tested & proven-to-last.

Color shown in photo may differ from actual product. * DesignWood Colorant may vary slightly depending on location, species of wood, age, grain pattern and heartwood content.

Jones Wholesale Lumber Company Inc.

10761 S. Alameda St., Lynwood, CA 90262 • 323-567-1301 • 323-566-4825 FAX • sales@joneswholesale.net

DesignWood

Pre-Colored ACQ Treated Lumber
Sedona Red

A Finished Project from the Start

DesignWood Color is part of the pressure-treating process.

Commercial Project Uses

- ▶ Pilings, Piers, Boardwalks, Bridges & Permanent Wood Foundations
- ▶ Structural Columns, Sign Posts, Utility Poles, Building Poles & Guardrails
- ▶ Sill Plates, Furring Strips, Shakes & Shingles

Agricultural Use

- ▶ Tomato & Grapevine stakes and Livestock Fencing
- ▶ Post Frame Structures, Pole Barns, Stables & Corrals

Residential Use & Homeowner Projects

- ▶ Decks, Porches, Arbors, Gazebos, Fences, Walkways & Retaining Walls
- ▶ Raised Beds, Planter Boxes, Outdoor Furniture, Picnic Tables & Play Sets

AWPA Use Category and Retentions for Preserve ACQ

AWPA Use Description	AWPA Use Category & Retention	Examples of Projects and Applications
INTERIOR/DRY (Interior, not in contact with ground or foundation)	UC1 .15 PCF	Interior furniture, millwork
INTERIOR/DAMP (Interior, subject to dampness)	UC2 .15 PCF	Interior beams, flooring, sill plate
ABOVE GROUND (Protected Exterior, above ground, coated)	UC3A .15 PCF	Coated millwork, siding, trim
ABOVE GROUND, EXPOSED (Exposed Exterior, above ground, may be finished)	UC3B .15 PCF	Decking, arbors, gazebos, walkways, railings, fence pickets
GROUND CONTACT (General Use Exterior, ground or freshwater contact)	UC4A .40 PCF	Fence posts, deck posts, raised beds
HEAVY DUTY GROUND CONTACT (Heavy Duty Exterior, ground or freshwater contact, saltwater splash zones, severe environments, high potential for deterioration)	UC4B .60 PCF	Utility poles, building poles, Permanent Wood Foundations, retaining walls, saltwater splash materials

Nails, Fasteners and Connectors

For the best results, the use of building-code approved, corrosion-resistant fasteners and connectors is always recommended for all exterior wood projects. Direct contact of Preserve®ACQ® treated wood with aluminum products is not recommended.

Hot-dipped galvanized fasteners (meeting ASTM A 153) and connectors (ASTM A 653 Class G185 sheet), or better, are recommended.

For Permanent Wood Foundations and corrosive environments, such as areas with saltwater spray, stainless steel fasteners are recommended.



Preserve®ACQ® is a NAHB Home Innovation Research Labs Green Certified Product for Resource Efficiency and is eligible to contribute points toward a building certification under the National Green Building Standard™. See our Preserve®ACQ® product listings on www.GreenApprovedProducts.com for more information.



Specifications and Approvals

Preserve®ACQ® Pressure-Treated Lumber and Plywood

Accepted and Standardized Preservative of The American Wood Protection Association (AWPA)



Proud Sponsor

▶ IBC & IRC Building Code compliant under AWPA Standards (U1 & T1)

▶ Use Categories:

Above Ground Use: UC1, UC2, UC3A, UC3B,
Ground Contact Use: UC4A, UC4B, UC4C

Look for **AWPA U1** and the **Checkmark of Quality** on the end tags of treated wood you buy as assurance the wood meets these tough standards.



Proper Use Application



- ▶ The AWPA is the leading authority on wood preservation science and only accepts qualified products into the AWPA Standards after meeting a vigorous review of performance and field-test data.
- ▶ The International Code Council's committees recognize AWPA Standards directly in the International Building Code (IBC) and International Residential Code (IRC) in applications where preservative treated wood is required.

Viance provides 3-part model specifications at www.TreatedWood.com

Safe Practices When Working With Pressure-Treated Wood

- ▶ Wear gloves when working with wood.
- ▶ Wear a dust mask when machining any wood to reduce the inhalation of wood dusts.
- ▶ Wear appropriate eye protection to reduce the potential for eye injury from wood particles and flying debris during machining.
- ▶ Wash hands thoroughly with mild soap and water after working with treated wood.
- ▶ All sawdust and debris should be cleaned up and disposed of after construction in accordance with local waste management regulations.
- ▶ Do not burn pressure-treated wood.
- ▶ Wash work clothes separately from other household clothing before reuse.
- ▶ Pressure-treated wood should not be used where it may come into direct or indirect contact with drinking water, except for uses involving incidental contact such as fresh water docks and bridges.
- ▶ Do not use pressure-treated wood in circumstances where the preservative may become a component of food, animal feed or beehives.
- ▶ Do not use pressure-treated wood for mulch.
- ▶ Treated wood may be disposed of in landfills or burned in commercial or industrial incinerators or boilers in accordance with federal, state and local regulations.

Preserve®ACQ® treated wood products are produced by independently owned and operated pressure treating wood facilities. * See Preserve®ACQ® Lifetime Limited Warranty at Treatedwood.com.

Preserve®ACQ® and Viance® are registered trademarks of Viance, LLC. AWPA is a registered trademark of the American Wood Protection Association. The Checkmark of Quality is a registered trademark of the Western Wood Preservers Institute (WWPI). All logos and trademarks are exclusive property of their respective owners. Viance®, LLC 2014. All rights Reserved. XXX 670W 012014



Viance, LLC
200 E Woodlawn Road,
Suite 350,
Charlotte, NC 28217

For more information,
Call 1-800-421-8661, or visit

treatedwood.com