

Preserve[®] and Preserve[®] Plus[®]

An environmentally advanced preservative system that provides long-term protection from decay and termites. For commercial, residential and agricultural uses in above ground, ground contact, fresh-water immersion and salt-water splash applications, Preserve is the proven wood preservative.

Preserve[®] ACQ[®]

- ▶ Long-term protection from decay and termite attack
- ▶ Twenty years of testing and field usage
- ▶ Environmentally friendly, Green Building Product
- ▶ Limited Lifetime Warranty



Preserve[®] Plus[®] ACQ[®]

Preserve Plus has the same benefits and warranty as Preserve, but also contains a built-in water repellent that reduces cracking, splitting and warping.



Preserve is a Green Approved Product listed by the NAHB Research Center and is eligible to earn points towards Green Certification under the National Green Building Standard.™





Painting and Staining or Natural Weathering

Preserve can be painted or stained to match any outdoor color scheme. High-quality oil and latex based paints and stains are recommended. Water repellent coatings can be applied to enhance the long-term weathering performance. It is important that the wood is dry and clean prior to applying any coating. Left uncoated, or with clear water repellent coatings, Preserve will initially weather to a natural brown color, eventually turning gray following long-term exposure to the sun.

Nails, Fasteners and Connectors

For the best results, use of building-code approved, corrosion-resistant fasteners and connectors is always recommended. Direct contact of Preserve treated wood with aluminum fasteners and fittings is not recommended.

Applications

- ▶ Decks
- ▶ Fencing
- ▶ Gazebos
- ▶ Raised Beds
- ▶ Pilings (freshwater)
- ▶ Steps
- ▶ Play sets
- ▶ Posts
- ▶ Landscaping
- ▶ Docks
- ▶ Walkways
- ▶ Sheds
- ▶ Trellis
- ▶ Lattice
- ▶ Sill Plates

Specifications

Viance provides 3-part model specifications at www.TreatedWood.com and at www.ARCAT.com.



Preserve® Plus® Offers Improved Weathering Performance

Wood exposed to the weather is subject to repeated wetting and drying cycles that cause it to swell and shrink, resulting in splitting, cracking and warping. Preserve Plus is protected with the combination of ACQ preservative treatment and a built-in water repellent to provide long-term protection against decay, termite attack and the effects of weathering.

Preserve Plus should be used for outdoor building projects where appearance is important and protection from the effects of weathering is a priority.



Get the free mobile app at <http://gettag.mobi>

Scan with mobile phone to visit www.TreatedWood.com

Preserve® is backed by a Lifetime Limited Warranty against decay and termite damage.

Product Features

- ▶ Provides long-term protection from decay and termite attack.
- ▶ Can be used in environmentally sensitive settings.
- ▶ Offers a wide selection of treatable timber species, including Douglas Fir.
- ▶ Easily painted or stained.
- ▶ Adherence to AWPA treatment standards is verified by independent third-party product inspection.
- ▶ Features a Limited Lifetime Warranty.

Treated Lumber and Plywood Specifications, Approvals, Registrations, and Awards

- ▶ **Standardized by the American Wood Protection Association**
Use Categories: U1, T1, UC1, UC2, UC3A, UC3B, UC4A, UC4B, UC4C
- ▶ **NAHB Research Center National Building Certified as a "Green Approved Product"**
- ▶ **ICC Evaluation Service Report (NER-643)**
- ▶ **Winner, 2002 US EPA Presidential Green Chemistry Award**
- ▶ Canadian Standards Association (CSA-O80)
- ▶ Japanese Industrial Standards (JIS)
- ▶ Australian/New Zealand AS/NZ Standard 1604
- ▶ Australian Quarantine and Inspection Service (AQIS)
- ▶ American Association of State Highway and Transportation Officials (AASHTO M-133)

Preserve® Recommended ACQ® Retentions For Various Applications

APPLICATION	RETENTION (LBS/CU.FT.)	TYPICAL USES
Above Ground	0.20	Decking components, 5/4" decking, fence boards, trim & fascia, framing, flooring, sill plates, trellises, gazebos, plywood
Ground Contact Fresh Water	0.40	Deck support posts, fence posts, landscaping, piers, docks, plywood
Critical Structural Members ²	0.60	Poles (building, transmission, and distribution), salt-water splash areas
Wood Foundation Systems	0.60	Wood foundations, crawl spaces

¹ The recommended ACQ retention levels for Preserve Plus are identical to Preserve treated wood as shown above.
² Pole approval for ACQ Type B.

© Viance (PD-03 2/11)



For more information, call 1-800-421-8661, fax us at 704-527-8232 or visit



Viance LLC • 200 E. Woodlawn Rd, Ste 350, Charlotte, NC 28217